



### UKCA Marking and Declaration of Performance

Allen Newport Ltd  
Marstons Pit  
Cavenham Road  
Tuddenham  
Bury St Edmunds, IP28 6SE

21

Reference: ANL2021/20-40mm

20-40mm G<sub>C</sub>80/20

EN 12620

### Declaration of Performance - Aggregates for Concrete

Aggregate	Type	Sand	
Particle Size	Designation	20-40mm G <sub>C</sub> 80/20	
Fines Content	Category	f <sub>1.5</sub>	
Particle Density Oven Dried	Declared Value	2.53	Mg/m <sup>3</sup>
Particle Density Saturated Surface	Declared Value	2.56	Mg/m <sup>3</sup>
Particle Density Apparent	Declared Value	2.6	Mg/m <sup>3</sup>
Water Absorption	Declared Value	1.1	%
Resistance to Fragmentation	Category	31	
Chlorides	Declared Value	0.00	%
Acid Soluble Sulfates	Category	0.50	
Total Sulfur	Declared Value	0.2	%
Water Soluble Sulfates	Declared Value	<0.01	%
Durability Against Freeze/Thaw	Declared Value	MS <sub>6</sub>	
Bulk Density Loose	Declared Value	1.37	Mg/m <sup>3</sup>
Bulk Density Rodded	Declared Value	1.44	Mg/m <sup>3</sup>

This Declaration of Performance is issued in accordance with Regulation (EU) No.305/2011, as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above, and is authorised and signed by:

Richard J Stevens  
Managing Director

Valid Date from:-

23rd March 2021